

# FOILEX MINI SKIMMER

The FOILEX Mini Skimmer is a portable unit for quick response to small spills from light to medium viscosity oils in harbours, lakes and rivers. Suitable for both advancing and stationary skimming operations, and due to its shallow draught allows skimming close to shorelines and in shallow waters. Also suitable, without its three pontoons, for fixed installation in API-tanks, pits etc.



- Equipped with the well proven self-adjusting flow controlled inlet weir.
- Always parallel to surface!
- Automatic compensation for waves and swell.
- Light weight and easy to use.
- Can be used with any type of vacuum pump with capacities up to 30 m<sup>3</sup>/h.

## Technical Specification

### Skimmer head

Capacity  
Discharge coupling  
Hopper entrance diameter  
Skimming gap  
Materials  
    Flotation frame  
    Pontoons  
    Hopper + inlet screen  
Draught  
Dimensions (L x W x H)  
Weight  
Shipping volume  
Shipping weight  
Inlet weir

### FOILEX Mini Skimmer

Up to 30 m<sup>3</sup>/h (135 USgpm), depending on available pump capacity  
Outer BSP thread R3" with Camlock male quick coupling  
Ø475 mm (Ø19 in)  
0 - 100 mm (0 - 4 in)  
  
Stainless steel  
Oil and chemical resistant polyethylene  
Stainless steel  
380 mm (15 in)  
1690 x 1530 x 600 mm (66 x 60 x 24 in)  
35 kg (74 lbs) 0,7  
m<sup>3</sup> (25 ft<sup>3</sup>) 68 kg  
(150 lbs)  
Flow controlled up/down adjustment with automatic parallel weir lip movement to surface.

### Hose package (optional)

Suction hose

Ø3" - 10 m spiral reinforced PVC vacuum hose to connect between Skimmer and pump unit.  
3" Camlock quick couplings in each end.  
2 x 5 litre plastic inflatable hose carrying floats.

Discharge hose

Ø3" 10 + 10 m flat type synthetic reinforced, covered and lined rubber hose to connect between Pump unit and storage facility.  
3" Camlock quick couplings in each end.

## Agent / Distributor:

NordTech Consulting & Trading Company, innehåller F-skatt. Rg. Nummer 969754-1093,  
Grona vagen 24A, 612 40 Finspang - Sweden

Phone: +46-122772111 / +46-763188020

E-mail: [info@nordtechconsulting.se](mailto:info@nordtechconsulting.se)

Website: [www.nordtechconsulting.se](http://www.nordtechconsulting.se)